

Package ‘omophub’

August 19, 2026

Title R Client for the 'OMOPHub' Medical Vocabulary API

Version 1.9.0

Description Provides an R interface to the 'OMOPHub' API for accessing 'OHDSI ATHENA' standardized medical vocabularies. Supports concept search, semantic search using neural embeddings, concept similarity, vocabulary exploration, hierarchy navigation, relationship queries, concept mappings, and FHIR-to-OMOP concept resolution with automatic pagination.

License MIT + file LICENSE

URL <https://github.com/omopHub/omophub-R>, <https://docs.omophub.com>,
<https://omophub.github.io/omophub-R/>, <https://omophub.com>

BugReports <https://github.com/omopHub/omophub-R/issues>

Depends R (>= 4.1)

Imports httr2 (>= 1.0.0), R6, rlang (>= 1.0.0), cli, tibble, purrr,
glue, checkmate

Suggests testthat (>= 3.0.0), httptest2, webmockr, knitr, rmarkdown,
keyring, withr

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

NeedsCompilation no

Author Alex Chen [aut, cre, cph],
Observational Health Data Science and Informatics [cph]

Maintainer Alex Chen <alex@omophub.com>

Repository CRAN

Date/Publication 2026-08-19 18:20:02 UTC

Contents

fhir_resolve	2
fhir_resolve_batch	3
fhir_resolve_codeable_concept	4
get_api_key	5
has_api_key	5
OMOPHubClient	6
omophub_fhir_url	8
set_api_key	9
Index	10

fhir_resolve	<i>Resolve a FHIR Coding to an OMOP standard concept</i>
--------------	--

Description

Standalone wrapper for client\$fhir\$resolve(). See [FhirResource](#) for full parameter documentation.

Usage

```
fhir_resolve(client, ...)
```

Arguments

- client An [OMOPHubClient](#) instance.
- ... Arguments passed to `FhirResource$resolve()`.

Value

A list with input and resolution.

See Also

[FhirResource](#), [fhir_resolve_batch\(\)](#), [fhir_resolve_codeable_concept\(\)](#)

Examples

```
## Not run:
client <- OMOPHubClient$new(api_key = Sys.getenv("OMOPHUB_API_KEY"))
fhir_resolve(
  client,
  system = "http://snomed.info/sct",
  code = "44054006",
  resource_type = "Condition"
)

## End(Not run)
```

fhir_resolve_batch	<i>Batch-resolve FHIR Codings</i>
--------------------	-----------------------------------

Description

Standalone wrapper for `client$fhir$resolve_batch()`. When `as_tibble = TRUE`, the result is a flat tibble suitable for dplyr/tidyr pipelines.

Usage

```
fhir_resolve_batch(client, ...)
```

Arguments

<code>client</code>	An OMOPHubClient instance.
<code>...</code>	Arguments passed to <code>FhirResource\$resolve_batch()</code> .

Value

See `FhirResource$resolve_batch()`.

See Also

[FhirResource](#), [fhir_resolve\(\)](#), [fhir_resolve_codeable_concept\(\)](#)

Examples

```
## Not run:
client <- OMOPHubClient$new(api_key = Sys.getenv("OMOPHUB_API_KEY"))
tbl <- fhir_resolve_batch(
  client,
  codings = list(
    list(system = "http://snomed.info/sct", code = "44054006"),
    list(system = "http://loinc.org", code = "2339-0")
  ),
  as_tibble = TRUE
)
dplyr::filter(tbl, status == "resolved")

## End(Not run)
```

`fhir_resolve_codeable_concept`*Resolve a FHIR CodeableConcept with vocabulary preference*

Description

Standalone wrapper for `client$fhir$resolve_codeable_concept()`.

Usage

```
fhir_resolve_codeable_concept(client, ...)
```

Arguments

<code>client</code>	An OMOPHubClient instance.
<code>...</code>	Arguments passed to <code>FhirResource\$resolve_codeable_concept()</code> .

Value

See `FhirResource$resolve_codeable_concept()`.

See Also

[FhirResource](#), [fhir_resolve\(\)](#), [fhir_resolve_batch\(\)](#)

Examples

```
## Not run:
client <- OMOPHubClient$new(api_key = Sys.getenv("OMOPHUB_API_KEY"))
fhir_resolve_codeable_concept(
  client,
  coding = list(
    list(system = "http://snomed.info/sct", code = "44054006"),
    list(system = "http://hl7.org/fhir/sid/icd-10-cm", code = "E11.9")
  ),
  resource_type = "Condition"
)

## End(Not run)
```

get_api_key	<i>Get OMOPHub API Key</i>
-------------	----------------------------

Description

Retrieves the OMOPHub API key from multiple sources in priority order:

1. Explicit argument
2. OMOPHUB_API_KEY environment variable
3. System keyring (if keyring package is installed)

Usage

```
get_api_key(key = NULL)
```

Arguments

key Optional explicit API key. If provided, this takes precedence.

Value

A character string containing the API key.

Examples

```
## Not run:
# From environment variable
Sys.setenv(OMOPHUB_API_KEY = "your_api_key")
key <- get_api_key()

# Explicit key
key <- get_api_key("your_api_key")

## End(Not run)
```

has_api_key	<i>Check if API Key is Available</i>
-------------	--------------------------------------

Description

Checks whether an OMOPHub API key is available without throwing an error.

Usage

```
has_api_key()
```

Value

TRUE if an API key is available, FALSE otherwise.

OMOPHubClient

OMOPHub API Client

Description

R6 class for interacting with the OMOPHub vocabulary service. Provides access to OHDSI ATHENA standardized medical vocabularies.

Details

The client provides access to these resources:

- concepts: Concept lookup and batch operations
- search: Basic and advanced concept search
- vocabularies: Vocabulary listing and details
- domains: Domain listing and concept filtering
- hierarchy: Ancestor and descendant navigation
- relationships: Concept relationships
- mappings: Concept mappings between vocabularies

Value

A new OMOPHubClient object.

Active bindings

concepts Access to concept operations.

search Access to search operations.

vocabularies Access to vocabulary operations.

domains Access to domain operations.

hierarchy Access to hierarchy operations.

relationships Access to relationship operations.

mappings Access to mapping operations.

fhir Access to FHIR-to-OMOP Concept Resolver operations.

Methods

Public methods:

- `OMOPHubClient$new()`
- `OMOPHubClient$print()`
- `OMOPHubClient$clone()`

Method `new()`: Create a new OMOPHub client.

Usage:

```
OMOPHubClient$new(  
  api_key = NULL,  
  base_url = NULL,  
  timeout = 30,  
  max_retries = 3,  
  vocab_version = NULL  
)
```

Arguments:

api_key API key for authentication. If not provided, reads from OMOPHUB_API_KEY environment variable or system keyring.

base_url API base URL. Defaults to `https://api.omophub.com/v1`.

timeout Request timeout in seconds. Defaults to 30.

max_retries Maximum retry attempts for failed requests. Defaults to 3.

vocab_version Optional vocabulary version (e.g., "2025.1"). If not specified, uses the latest version.

Method print(): Print client information.

Usage:

```
OMOPHubClient$print()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OMOPHubClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:  
# Create client (uses OMOPHUB_API_KEY env var)  
client <- OMOPHubClient$new()  
  
# Or with explicit API key  
client <- OMOPHubClient$new(api_key = "your_api_key")  
  
# Search for concepts  
results <- client$search$basic("diabetes")  
  
# Get a specific concept  
concept <- client$concepts$get(201826)  
  
# Use specific vocabulary version  
client <- OMOPHubClient$new(vocab_version = "2025.1")  
  
## End(Not run)
```

omophub_fhir_url	<i>OMOPHub FHIR Terminology Service URL</i>
------------------	---

Description

Convenience helper for constructing the OMOPHub FHIR Terminology Service base URL for a given FHIR version. Use it when configuring an external FHIR client library (httr2, fhircrackr, etc.) to talk to OMOPHub's FHIR endpoint directly.

Usage

```
omophub_fhir_url(version = c("r4", "r4b", "r5", "r6"))
```

Arguments

version FHIR version prefix. One of "r4" (default), "r4b", "r5", or "r6".

Value

A character scalar with the full FHIR base URL, e.g. "https://fhir.omophub.com/fhir/r4".

Examples

```
omophub_fhir_url()
omophub_fhir_url("r5")

## Not run:
# Use with httr2 to call the $lookup operation directly
library(httr2)
req <- request(omophub_fhir_url()) |>
  req_url_path_append("CodeSystem/$lookup") |>
  req_url_query(
    system = "http://snomed.info/sct",
    code = "44054006"
  ) |>
  req_headers(Authorization = paste("Bearer", Sys.getenv("OMOPHUB_API_KEY")))
resp <- req_perform(req)

## End(Not run)
```

set_api_key	<i>Set OMOPHub API Key</i>
-------------	----------------------------

Description

Stores the OMOPHub API key in the specified location.

Usage

```
set_api_key(key, store = c("env", "keyring"))
```

Arguments

key	The API key to store.
store	Where to store the key. One of: • "env": Set as environment variable for current session (default) • "keyring": Store securely in system keyring (requires keyring package)

Value

Invisibly returns TRUE on success.

Examples

```
## Not run:  
# Store in environment (current session only)  
set_api_key("your_api_key")  
  
# Store securely in keyring (persistent)  
set_api_key("your_api_key", store = "keyring")  
  
## End(Not run)
```

Index

fhir_resolve, [2](#)
fhir_resolve(), [3](#), [4](#)
fhir_resolve_batch, [3](#)
fhir_resolve_batch(), [2](#), [4](#)
fhir_resolve_codeable_concept, [4](#)
fhir_resolve_codeable_concept(), [2](#), [3](#)
FhirResource, [2–4](#)

get_api_key, [5](#)

has_api_key, [5](#)

omophub_fhir_url, [8](#)
OMOPHubClient, [2–4](#), [6](#)

set_api_key, [9](#)